


$\phi$	0080	0100	0115	0120	0130	0140	0150	0160	0180	0200	0225	0250	0300	0350	0400	0450	0500	0550	0600
<b>B</b>	195	215	230	235	245	255	265	275	295	315	340	365	415	465	515	565	615	665	715
<b>C</b>	230	250	265	270	280	290	300	310	330	350	375	400	450	500	550	600	650	700	750
<b>E</b>	645	665	680	685	700	710	720	730	750	770	800	825	880	930	985	1040	1090	1145	1200
<b>F</b>	630	650	665	670	680	690	700	710	730	750	775	800	850	900	950	1000	1050	1100	1150
<b>kg</b>	2,7	2,9	3	3,1	3,2	3,3	3,3	3,5	3,6	3,9	4,1	4,3	4,9	5,4	6	6,5	7,1	7,7	8,3

notes:

DIN ISO 13920 Tolerances B			
revisions-no.			
date	name		
drawn by	20.02.20	JMA	
checked by	20.02.20	SWA	
approved by	20.02.20	JWY	
modified by			

 CHIMNEY SYSTEMS		description	Flashing kit 16-25°, incl.storm collar
		code	DWECO82
drawing-no.		02-35-5303-000	

scale	1:12
format	A4
sheet	1 of 1
